

Specifications



General		
Frequency Range		UHF: 400–470MHz VHF:136–174MHz
Channel Capacity		16
Channel Capacity		25/20/12.5 kHz
Operating Voltage		13.6 ± 15% V DC
Current Drain	Standby	1.2A
	Transmit	12A
Frequency Stability		± 1ppm
Antenna Impedance		50Ω
Duty Cycle		100%
Dimensions (W×H×D)		483 X 88 X 366 mm
Weight		8.5 Kg
LCD Display		220X176 pixels; 262,000 colors

Receiver	
Sensitivity(Analog)	0.3 μ V (12dB SINAD) 0.22 μ V (Typical) (12dB SINAD) 0.4 μ V (20dB SINAD)
Sensitivity(Digital)	0.3 μ V/BER5%
Blocking	100dB
Adjacent Channel Selectivity	
TIA-603	65dB @ 12.5 kHz / 75dB @ 20/25 kHz
ETSI	65dB @ 12.5 kHz / 75dB @ 20/25 kHz
Intermodulation	
TIA-603	75dB@12.5/20/25KHz
ETSI	70dB@12.5/20/25KHz
Spurious Response Rejection	
TIA-603	85dB@12.5/20/25KHz
ETSI	80dB@12.5/20/25KHz
Hum and Noise	40dB @ 12.5 kHz 43dB @ 20 kHz 45dB @ 25 kHz
Rated Audio Power Output	0.5W
Audio Distortion	3%
Audio Response	+1 ~ -3 dB
Conducted Spurious Emission	-57 dBm

Transmitter	
RF Power Output	5–50W (Continuous)
FM Modulation	11KΦF3E @ 12.5 kHz 14KΦF3E @ 20 kHz 16KΦF3E @ 25 kHz
4FSK Digital Modulation	12.5kHz Data Only: 7K6ΦFXD 12.5kHz Data & Voice: 7K6ΦFXW
Conducted/Radiated Emission	-36dBm <1GHz -30dBm >1GHz
Modulation Limiting	± 2.5kHz @ 12.5 kHz ± 4.0 kHz @ 20 kHz ± 5.0kHz @ 25 kHz
FM Hum and Noise	40dB @ 12.5 kHz 43dB @ 20 kHz 45dB @ 25 kHz
Adjacent Channel Power	60dB @ 12.5 kHz 70dB @ 20/25KHz
Audio Response	+1 ~ -3dB
Audio Distortion	3%
Digital VocoderType	AMBE++/SELP

Environmental Specifications	
Operating Temperature	-30℃ ~ +60℃
Storage Temperature	-40℃ ~ +85℃

All Specifications are tested according to applicable standards, and subject to change without notice due to continuous development.



RD988
Powerful Digital Repeater

As a professional repeater built to the DMR standard, RD988 integrates user concerns and actual requirements. Powerful digital feature, remarkable service quality and considerate ergonomic design. It will refresh your communication experience!



- Smart A/D Detection, Smooth Migration
- Outstanding Reliability



www.hytera.cn
Hytera Communications Corporation Limited

HYT is a registered trademark of Hytera
© 2010 Hytera, Co., Ltd. All Rights Reserved.

HYTERA retains right to change the product design and specification. Should any printing mistake occur, HYTERA doesn't bear relevant responsibility. Little difference between real product and product indicated by printing materials will occur by printing reason.

Address: HYT Tower, Hi-Tech Industrial Park North, Beihuan RD., Nanshan District, Shenzhen, China
Tel : +86-755-2697 2999 Fax : +86-755-8613 7139 Post : 518057

20101027R2V1(EN)

www.hytera.cn

Higher Efficiency Richer Experience



Features »

2RU

Standard 19" , 2RU rack-mount design, compatible with desktop housing as well

LED

Colored LEDs for clear status indication



Advanced heat sink design with thermal-controlled cooling fan



Ergonomics handle design makes handling more comfortable



Programmable buttons for customized application



2.0" TFT LCD and menu navigation knob to facilitate service and maintenance



Internal installation for mobile duplexer



Product Features »



Smart Analog & Digital Auto Detection

This repeater supports digital and analog modes. It can smartly select the right one based on the type of received signal, allowing you to enjoy digital delights with ease.

Advanced TDMA Technology

The application of Time Division Multiple Access (TDMA) technology greatly enhances spectrum efficiency, which allows twice the user compared with that of traditional FDMA. Obviously, this can not only save your cost in infrastructure and frequency license, but also relieve the pressure of increasing shortage in spectrum resources.



Outstanding Reliability

- The repeater is capable of 100% duty cycle at full power (50W), meeting demanding requirements of any conventional or trunking system.
- As a modularized product built to military standard, the repeater can deliver solid reliability and remarkable performance for a long time.
- The unique heatsink design combining a built-in heat pipe and a temperature-controlled fan ensures quick heat dissipation, enabling the repeater to work normally even with full power.



Handy Management Service

With the management software, you can remotely monitor and diagnose a repeater. In addition, you can either record or play back the audio freely in digital mode.

Innovative LED Design

The innovative LED and the 2.0" HD color display would deliver you the repeater status clearly, as well as a pleasing visual experience.

Standard Accessories »



DC Power Cable
PWC11

Optional Accessories »



Programming Cable
(USB Port) PC37



Palm Microphone
SM16A1



Omnidirectional
Antenna



Directional Antenna



Duplexer Installation Kit
(Apply to Hytera-approved
Model Only)



Desktop Power Supply (300W)
PS22002



Rack-mount Installation
Kit (For Ps22002 only)
BRK12

