



PR9530/FR9530

Dual-band Radio

- V/UHF dual-band
- Voice relay and Ad-hoc networking
- Small, compact and usable design
- Secure voice and data



PR9530 Handheld Radio



FR9530 Vehicular Radio

Overview

The dual-band radio works in V/UHF covering 108MHz to 174MHz and 225MHz to 400MHz. The Small Form Factor(SFF) portable radio easily fits in a pocket. Based on the SDR architecture design, the radio integrates the excellent tactical features, such as voice relay, Ad-hoc networking and FH, it can provide a stable communication in complex terrain. The radio also can be used in ground-to-air communication with AM mode.

Application Scenario



The radio offers Ad-hoc networking capabilities including automatic multi-hop services for voice and data. VRN extends voice communication distance, resolves the communication issues in complex terrain, for example underground, jungle and trench.

Specification

General	
Frequency Range	108-174MHz, 225-400Mhz
Channels Spacing	25kHz
Net Preset	100 total/15 selectable from switch
Data Rate	≤48kbps
Data Interface	RS232/Ethernet
Weight	Handheld: ≤0.34kg(with battery) Vehicular: ≤18kg
Dimension (HXWXD, mm)	Handheld: 152×61×36.5(with battery) Vehicular: 19", 2U
Waveforms and COMSEC	
Waveforms	CNR/VRN/PRN
Voice and Data Modes	AM/FM/GMSK/CPM
COMSEC	AES-256/Customized
ECCM	FH/FCS
Max. Hopping Rate	1,000hops/s
Networking capability	32-node, 6-hop

Accessories



Steel Tape Antenna



2500mAh Battery



Charger



Power Adapter



The radio have ground-to-air mode, supports V/UHF dual-band frequency and AM voice. The radio combines in a small form factor secure and flexible architecture with excellent RF performance. It can be used to direct take off, landing and target guidance.

Transmitter	
Output Power	Handheld: FM: 0.5/2/3W; AM: 1.5W Vehicular: FM: 5/50/100W; AM: 50W
Receiver	
Sensitivity	≤-118dBm (SINAD=12dB, FM) ≤-106dBm (SINAD=10dB, AM)
Environmental	
Storage Temperature	-40°C~70°C
Operating Temperature	-30°C~60°C
Immersion	Handheld: 2m, 4h
Shock & Vibration	MIL-STD-810G
Electromagnetic	MIL-STD-461F

All specifications are tested according to applicable standards and subject to change without notification due to continuous development.